

STANDARD FLY SCREEN

A powder coated aluminium frame complete with fibreglass mesh as standard. This screen is of a mitred construction with extruded aluminium corner keys for strength. The mesh is held in place with a pliable rubber gasket which is designed to keep the mesh taut and secure. This screen is fitted on lift off hinges and turn buttons and is easy removed for cleaning and servicing.



**A COST EFFECTIVE FLYSCREEN SYSTEM
THAT CLEANS UP THE HYGIENE LEGISLATION**

STANDARD FLYSCREENS

<u>How they work</u>	This screen has the facility to accept different thickness of brush pile into the back of the frame. These then form a seal between the back of the screen and the face of the window.
<u>Suitability</u>	<p>This screen can be fitted over any UPVC, timber or metal casements. Sometimes, it is necessary to use our special plastic build off sub-frame to clear existing handles. Fibreglass mesh is fitted as standard, but stainless steel or aluminium mesh can be fitted where required.</p> <p>This screen is usually fitted internally, however, because of the durable powder coating, it can be fitted to any external application.</p>
<u>Removal</u>	Release turn buttons, hinge open and lift off.
<u>Maintenance</u>	<p>The powder coating can be cleaned with a cream cleaner to restore its original condition. All meshes can be cleaned with warm, soapy water to remove grease or dirt.</p> <p>Dusty screens should be vacuumed or brushed clean.</p>
<u>Technical</u>	<p>Standard colours – White to BS9010 and brown to BS8017 The standard range of colours can be matched at extra cost.</p> <p>Fibre mesh – 18 x 14 weave, charcoal, ventilation 66%</p> <p>Fibre mesh – 20 x 20 weave, charcoal, ventilation 32%</p> <p>Stainless steel – 18 x 14 weave, charcoal, ventilation 66%</p> <p>Aluminium - 18 x 14 weave, charcoal, ventilation 66%</p>
<u>Guarantee</u>	12 months on all workmanship under normal wear and tear.