

STANDARD DOOR

A powder coated aluminium framed door. Each corner is mitred and riveted through corner cleats for maximum strength. 125mm push and kick plates fitted to the middle and bottom of the door add to the strength and durability. The door is operated with a central door closer to make sure the door is kept shut when in use. Fibre glass mesh is held in place with a pliable rubber gasket designed to keep the mesh tight and secure. This door can be upgraded with stainless steel mesh.



**A COST EFFECTIVE FLY SCREEN SYSTEM
THAT CLEANS UP THE HYGIENE LEGISLATION**

STANDARD FLY SCREEN DOOR

<u>How they work</u>	A single action door designed to work in front of, or behind the existing door and can be hinged to the existing framework or to our plastic sub-frame if you need to clear handle obstructions. Comes complete with its own automatic closure.
<u>Suitability</u>	This door can be fitted to UPVC, timber or metal casings which makes it ideal for domestic or commercial use with light traffic. Fly mesh will only push out or come loose if the push and kick plates are not used when opening the door. If you think this is a possibility you should upgrade to a heavy-duty door, which will include a strong decorative grill, designed to protect the mesh.
<u>Removal</u>	Door and closure can be removed without the use of specialised tools.
<u>Maintenance</u>	The door closure is maintenance free. To keep the door hinges working effectively, spray WD40 or a little light machinery oil into the moving parts periodically. The powder coating can be cleaned with a cream cleaner to restore its original condition. All meshes can be cleaned with warm, soapy water to remove grease or dirt. Dusty screens should be vacuumed or brushed clean.
<u>Technical</u>	Standard colours – White to BS9010 and brown to BS8017 The standard range of colours can be matched at extra cost. Fibre mesh – 18 x 14 weave, charcoal, ventilation 66% Fibre mesh – 20 x 20 weave, charcoal, ventilation 32% Stainless steel – 18 x 14 weave, charcoal, ventilation 66% Aluminium - 18 x 14 weave, charcoal, ventilation 66% Standard sizes up to 2.1 metres high x 1 metre wide.
<u>Guarantee</u>	12 months on all workmanship under normal wear and tear.